# Steel Commercial Circulating Pedestal Fan 24 In. Black/Silver

**MODEL CCRF-24-P**

Facilities Maintenance / Commercial Circulator Fans

## PRODUCT OVERVIEW

The two speed commercial circulating is perfect for a variety of industries. The pull chain switch give the user functional control. These portable blowers do not have a totally enclosed motor. The guard is coated steel with retaining clips. The fan has a steel hub and aluminum paddle blades. The motor is permanently lubricated with a permanent split capacitor.

## KEY FEATURES

- Meets OSHA standards and is UL C/US listed
- Three blade design keeps are moving
- Use in a clean and dry commercial application
- Wide circular pedestal base

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 63 lbs | 27" W x 27" L x 104" H | 63 lbs |

| PACKAGE 1 SIZE | COLOR / FINISH | FREIGHT TYPE |
|---|---|---|
| 8" W x 33" D x 35" H | Black / Silver | Parcel |

**AVAILABILITY** Quote Required - Please Contact Sales **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Blade Diameter (in.)** | 25 |
| **Mounting Style** | Pedestal |
| **Amps High** | 2.3 |
| **CFM High** | 5400 |
| **CFM Low** | 4300 |
| **Electric Motor Horsepower** | 1/4 |
| **Conductor Cord Length (in.)** | 108 |
| **Conductor Cord** | SJT type 3 |
| **Voltage/Phase** | 120V/1PH |
| **CFM Medium** | 4900 |
| **OSHA** | 1910.212 (a)(5) |
| **Lowest Pole Position (in.)** | 43 |
| **Highest Pole Position (in.)** | 6 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Gary, TN 37615**

Warranty: **90 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=123