

# Steel Top Mount Floor Lock 7 to 8 In. Height 2,000 Lb. Capacity Silver

**MODEL FL-LK-6EH**

Facilities Maintenance / General Purpose Floor Locks

## PRODUCT OVERVIEW

Floor locks may be used on platform trucks, fixture dollies, or equipment with casters. Simple foot pressure immobilizes equipment. Locks when large friction face is pressed against the floor. To release simply kick release rod. Brake is independent of casters and can be installed to any convenient location on the cart. Vertical mounting plate designed to mount to sides of carts and other portable products. The spring loaded pad accommodates uneven floors. Units mount with pad 1." off the floor when retracted.

## KEY FEATURES

- Lock constricts movement of unit
- Attachable to moving platform carts
- Simple locking and unlocking function
- Able to be used on rough surfaces

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**6 lbs**

ASSEMBLED SIZE  
**8" W x 7.5" L x 5" H**

SHIP WEIGHT  
**7 lbs**

PACKAGE 1 SIZE  
**6" W x 8" D x 9" H**

COLOR / FINISH  
**Silver**

FREIGHT TYPE  
**Parcel**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                          |               |
|------------------------------------------|---------------|
| Capacity (lbs.)                          | 2,000         |
| Mounting Height (in.)                    | 8             |
| Retracted Height (in.)                   | 7             |
| Used with Caster Size (in.)              | 6             |
| Pad Mounting Height Retracted (in.)      | 1-1/2         |
| Type                                     | Foot pedal    |
| Mounting Type                            | Top Plate     |
| Base Plate Width (in.)                   | 5             |
| Base Plate Length (in.)                  | 7-1/2         |
| Base Plate Mounting Holes (qty.)         | 4             |
| Slotted Mounting Hole Width/Height (in.) | 1/2 x 1-1/8   |
| Inside Bolt Hole Spacing (in.)           | 3-1/8 X 5-3/8 |
| Outside Bolt Hole Spacing (in.)          | 4 X 6-1/4     |
| Plate Thickness (in.)                    | 3/8           |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1066>